

# Aqua Mix® Enrich 'N' Seal™

## 1 Product Name

Aqua Mix® Enrich 'N' Seal™

## 2 Manufacturer

Custom Building Products  
13001 Seal Beach Blvd.  
Seal Beach, CA 90740-2757  
Customer Support: 800-272-8786  
Technical Services: 800-282-8786  
Fax: 800- 200-7765  
Email: [contactus@cbpmail.net](mailto:contactus@cbpmail.net)  
[custombuildingproducts.com](http://custombuildingproducts.com)



## 3 Product Description

A premium, no-sheen, enhanced-look, 100% polymer-solid, penetrating sealer formulated to darken, enrich, and highlight the character and beauty of unsealed natural stone.

Key Features:

- Rejuvenates the color and improves the appearance of worn and weathered stone
- May also be used as a pre-grouting sealer
- Allows moisture-vapor transmission
- Effectively seals and darkens the color of grout joints

### Uses

- Unsealed natural stone such as marble, granite, slate, limestone, travertine, quartzite, and sandstone
- Effective for interior and exterior applications

### Benefits of Product in the Installation

Complies with all Federal EPA and SCAQMD standards for VOC

### Limitations to the Product

- Do not allow sealer to come in contact with any non-recommended surface as product is not completely removable
- Sealers and finishes should not be used before or after use of Enrich'N'Seal™
- If Enrich'N'Seal™ is not wiped completely dry within 5 minutes, a residue may form. If residue occurs, use a scrub brush or floor machine with Aqua Mix® NanoScrub® or Heavy-Duty Tile & Grout Cleaner to remove sealer residue. Always try a small test area to ensure results. If results are not satisfactory, contact Technical Services for additional options
- Keep floor surfaces dry and clean to reduce possibility of slip-fall accidents. Routine pressure-washing will affect expected wear
- Sealers will not prevent surface wear or etching from acids or caustic chemicals

## 4 Technical Data

### Technical Chart

Property	Test Method	Requirement	Typical Results
Stain Resistance	CTI-072	n/a	Excellent
pH			n/a
Darken Stone			Yes
Cure Time			48 Hours
Expected Wear			Up to 15 Years

## 5 Instructions

### General Surface Prep

Surface should be dry, clean and free of waxes, sealers, or finishes. Do not apply directly over silicone sealers, oil or wax based finishes. **TileLab® Heavy-Duty Stripper & Cleaner will clean the surface and remove wax or old acrylic finishes.** Place a few drops of water on various tiles. If water doesn't penetrate, additional removal is necessary. **Gloss Sealer & Finish can be applied over any TileLab® sealer except Stone Sealer & Enhancer.** New installations need to be cured at least 48 hours before application. Clay and Saltillo tile may require extended drying time depending on temperature and humidity. Make sure the tiles are completely dry before application. Test product in obscure area to ensure desirable results.



# CUSTOM®

# Aqua Mix® Enrich 'N' Seal™

## Application of Product

Read entire label before using. For new installations, sealer can be applied to a dry surface as soon as 72 hours after grouting. Surface must be clean, dry, and free of existing sealers or coatings. Apply using a sponge, brush, paint pad, cotton towel, or sprayer. NOTE: Avoid overlapping and rundown. On vertical surfaces, apply bottom to top or apply to each tile prior to installation. Be sure any sealer that does not penetrate surface is polished dry off surface within 5 minutes of each application using absorbent paper or cotton towels. If sealer residue is not completely removed from stone and grout surface within 5 minutes of application, a residue may form. If 2 or more coats are applied, allow a minimum of 30 minutes drying time between applications. Some highly porous surfaces may require an additional application after full cure insuring that all residue is removed within 5 minutes. Clean applicator tools with mineral spirits after each use.

## Pre-Grouting Application

Apply over clean stone or tile a minimum of 16 hours prior to grouting - follow application procedures above.

## Drying Time

Ready for surface traffic in 12 hours after final application. Keep dry for 12 hours. Achieves full cure in 48 hours.

## Cleaning of equipment

Clean tools and hands with soap and water immediately after use.

## Storage

- Close container tightly after each use
- Store in original container only
- Store and use between temperatures of 40°F - 90°F (4°C - 32°C)
- Dispose of residue or any unused leftover product in accordance with applicable federal, state, and local requirements

## Health Precautions

FLAMMABLE. MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. Keep away from heat and sources of ignition. Wear skin and eye protection. Do not breathe vapor or spray. Contains alkyl alkoxy silane. If in eyes, flush with water for at least 15 minutes. If on skin, wash with soap and water. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting, seek medical attention.

## 6 Availability & Cost

Product Name	Location	Item Code	Size	Package
Aqua Mix® Enrich 'N' Seal	USA	100250	1 pt (473 ml)	Bottle
	USA	100251-4	1 qt (946 ml)	Bottle
	USA	100252	1 gallon (3.8 L)	Bottle
	Canada	C100250	1 pt (473 ml)	Bottle
	Canada	C100251-4	1 qt (946 ml)	Bottle
	Canada	C100252	1 gallon (3.8 L)	Bottle

## 7 Product Warranty

Custom® Building Products warrants to the original consumer purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. Custom's® sole liability under this warranty shall be limited to the replacement of the product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with Custom's® printed instructions. Custom® makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country/territory to another. Click for details and complete [warranty information](#).

## 8 Product Maintenance

Use an appropriate TileLab® or Aqua Mix® neutral cleaner for routine cleaning.

## 9 Technical Services Information

For technical assistance, contact Custom® Building Products.

## 10 Filing System

Additional product information is available from the manufacturer upon request.

## Expected Wear

EXPECTED WEAR UP TO 15 YEARS

- Will vary depending on hardness and texture of surface, type of area, surface wear, frequency, and type of maintenance products used
- Exterior applications may require more frequent reapplications
- Weather conditions, harsh cleaning methods, and high-alkaline, acidic, or solvent-based cleaners will affect wear



# CUSTOM®

# Aqua Mix® Enrich 'N' Seal™

---

## Related Products

Aqua Mix® Concentrated Stone & Tile Cleaner

Aqua Mix® AquaKleen™



**CUSTOM®**

# Aqua Mix® Enrich 'N' Seal™

---

## Coverage

Depends on type of stone or tile, porosity and texture of surface, temperature, humidity, and method of application.

Size	Min Coverage	Max Coverage
1 Gallon (3.78 L)	500 sq. ft. (46 M <sup>2</sup> )	1,500 sq. ft. (140 M <sup>2</sup> )