Aqua Mix® Reviver®

1 Product Name

Aqua Mix® Reviver®

2 Manufacturer

Custom Building Products 13001 Seal Beach Blvd. Seal Beach, CA 90740-2757 Customer Support: 800-272-8786 Technical Services: 800-282-8786

Fax: 800- 200-7765 Email: contactus@cbpmail.net custombuildingproducts.com

3 Product Description

A user-friendly, highly-effective, ready-mixed paste for polish restoration and maintenance of worn, calcium-based, polished stone.

Suitable Tile Types

Polished limestone, marble, travertine and cement-based precast terrazzo

Limitations to the Product

- Do not allow product to come in contact with any non-recommended surface
- May not be suitable for some green marbles
- Severely damaged or worn polished marble may require professional resurfacing
- Not intended for use on granite, porcelain, ceramic tile or cultured marble

4 Technical Data

Technical Properties Chart

- · Paste consistency
- pH 1-2
- Complies with all Federal EPA and SCAQMD standards for VOC

5 Instructions

General Surface Prep

Test a small area according to application instructions to determine desired results.

Equipment

- 175 to 300 RPM floor machine or hand polish machine
- · Natural hair or synthetic fiber tan floor pads
- Reviver®
- · Protective plastic or blue painter's tape
- · Spray bottle of water
- Wet/dry vacuum
- Mop and bucket
- Squeegee



Application of Product

Read entire label before using. MIX WELL before using. Sweep or vacuum surface. Surface to be polished must be free of existing sealers or coatings. Protect baseboards, carpet, etc. with protective plastic and/or blue painters tape. Wet an area no larger than 20 ft (2 M)with clean water and place 2 tablespoons of Reviver® in the center. Using a natural hair or synthetic fiber tan floor pad, work the area in a side-to-side motion with a 175 to 300 RPM floor machine. The consistency of the slurry should be fluid enough to achieve even coverage. If the slurry becomes too dry, add water as required. For large areas, work in small sections and be sure to overlap the sections to achieve an even polish. Continue until the required polish has been achieved - squeegee slurry from a small area to check for desired results prior to removing slurry. Use a wet-dry vacuum to remove slurry and rinse thoroughly. Polish dry with a new polishing pad or cotton bonnet.

NOTE: An even higher shine can be achieved by using Marble Re-Polish.

Cleaning of equipment

Clean tools and hands with water before material dries.

Health Precautions

CORROSIVE. CAUSES BURNS. HARMFUL IF SWALLOWED. Wear skin and eye protection. Do not breathe dust. Contains potassium oxalate. If in eyes, flush with water for at least 15 minutes. If on skin, wash with soap and water. If respiratory tract is irritated, move to fresh air. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting, seek medical attention. KEEP OUT OF REACH OF CHILDREN.

6 Availability & Cost

Location	Item Code	Size	Package
USA	100530	10 lb (4.54 kg)	Tub



Published Date: 7/3/2013

TILING 09 30 00 Aqua Mix® / TDS-171

Aqua Mix® Reviver®

7 Product Warranty

Custom® Building Products warrants to the original consumer purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. Custom's® sole liability under this warranty shall be limited to the replacement of the product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with Custom's® printed instructions. Custom® makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country/territory to another. Click for details and complete warranty information.

8 Product Maintenance

Properly installed product requires no special maintenance.

9 Technical Services Information

For technical assistance, contact Custom® Building Products.

10 Filing System

Additional product information is available from the manufacturer upon request.

Handling & Storage

- Close container tightly after each use
- · Store in original container only
- Store in and use in temperatures between 40° F 90° F (4° C 32° C)
- Store in areas inaccessible to small children
- Do not reuse empty container, wrap and discard in trash or recycle

Related Products

Aqua Mix® Renue®

Published Date: 7/3/2013



TILING 09 30 00 Aqua Mix® / TDS-171

Aqua Mix® Reviver®

Coverage

SIZE	Min Coverage	Max Coverage
1 lb (.45 kg)	200 sq. ft. (19 M²)	300 sq. ft. (28 M²)



Published Date: 7/3/2013